Cloud 9X IP

A compact, IP-rated low-lying fogger that creates dense, floor-hugging fog using only tap water and specialized fluid, eliminating the need for dry ice or CO2.
Ideal for professional touring productions, event stages, and ballrooms requiring a reliable, continuous low-fog effect without the logistical challenges of dry ice.

- Generates continuous low-lying fog capable of covering a 3,230 square foot area.
- Reaches operational temperature in just five minutes for rapid event deployment.
- Automates refilling with a direct garden hose connection for unattended operation.
- Offers versatile control via DMX, RDM, onboard display, and included wireless remote.
- Housed in a rugged, integrated flight case with a stackable design for touring.
- Simplifies cleanup using an integrated water drainage system with a durable brass fitting.

SPECIFICATIONS

Dynamic Effects

Fan Performance: 81 cfm

Low Fluid Shutdown: Yes

Construction / Physical

Dimensions:

Dimensions (without back cover):	30 x 17.36 x 19.22 in (762 x 441 x 488.1 mm)
Dimensions (with back cover):	37.72 x 17.36 x 19.22 in (958 x 441 x 488.1 mm)

Output Nozzle (Outer Diameter): 4.76 in (121 mm)

Hose Length (Fully extended): 11 ft (3.4 m)

Weight: 76.6 lb (34.75 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, High-impact flame-retardant polymer

Water Tank Capacity:

(Primary Tank): 4.91 gal (18.6 L)
(Reserve Tank): 2.41 gal (9.1 L)
(Total): 7.32 gal (27.7 l)

Tank Capacity (Low-lying Fog Fluid): 0.8 gal (3 l)

Fog Fluid Consumption: 25 mL/min (0.88 fl oz/min)

Fog Fluid Runtime (Fog Fluid Tank,3 L): 2 hr

Water Consumption: 184.7 mL/min (6.25 fl oz/min)

Water Runtime (w/ Total Water Tank, 27.7 L): 2.5 hr

Connections

Power Input: Seetronic Powerkon IP65

Data Connectors: 3-pin/5-pin IP rated

Cable Length (power): 5 ft (1.5 m)

Firmware upgrades: USB type-C

Control

Control Protocol: DMX, RDM, Wireless Remote

DMX Channels: 3

Modes/Personalities: 1 personality (3ch)

On-Board Control: Yes

Included Remote: Yes

Electrical

Input Voltage: 120 VAC, 60 Hz

Input Voltage: 230 VAC, 50 Hz

Power and Current: 1960 W, 17.5 A @ 120 V, 60 Hz

Power and Current: 1281 W, 5.59 A @ 230 V, 50 Hz

Heat-up Time: 5 min

Breaker Size: 10 A, 250 V

Certifications / Qualifications

Certifications: CE, ROHS, UKCA

IP Rating: IP53, temporary outdoor/wet use

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Required Accessories

Accessories (required): Fog Fluid-LLG
Compatible Mounting Options: Floor Mount/Positioning only w/locking wheels

Optional Accessories

Neutrik powerKON cables
DMX Cables

What's Included

Cloud 9 X IP
Seetronic Powerkon IP65 power cable
RF remote (2-button)
2 pcs. hose clamps, 6 in (152 mm) diameter
Barbed hose adapter (0.5 in) (13 mm) diameter
2 pcs. barbed hose adapter hose clamp 1 in(25 mm) diameter
6ft (2m) output hose, 5 in, (130 mm) diameter
Removable rear cover
Hose coupler, 5 in (130mm) diameter
Floor nozzle, 5 in (130mm) diameter
Overfill hose (polyurethane, 6mmOD, 4mm ID, 80 in / 204 cm)
Quick Reference Guide