



WELL FIT X

The WELL FIT X is an upgraded workhorse uplight featuring increased lumen output, improved color mixing, and enhanced functionality like beam shaping and a décor-matching cover in a more compact and lightweight design.

Ideal for any indoor or outdoor production, its road-worthy six-unit kit with integrated charging allows for rapid deployment and easy management in any event environment.

- Delivers vibrant color mixing with nine RGBWW LEDs and a 2600K to 10,000K CCT range.
- Built with an IP65-rated housing and Gore valve for reliable all-weather operation.
- Offers versatile wireless control options including CRMX, RDM, NFC, and an included RF remote.
- Provides selectable battery runtimes of 5, 8, 12, or 18 hours at full output.
- Allows software updates via USB-C while fixtures remain inside the charging case.
- Features adjustable PWM for flicker-free on-camera use and a high-contrast OLED display.

SPECIFICATIONS

Optical

Light Source: 9 LEDs (RGBWW) 13.2 W, (556 mA), 50,000 hours life expectancy

Color Temperature (range): 2600 to 10,000K

Beam Angle: 11.5°

Field Angle: 19.1°

Cutoff Angle: 30.9°

Lumens: 2289 lm (AC Power)

Illuminance: Illuminance: 1651 lux @ 5 m (AC Power)*

Lumens: Lumens: 2369 lm (OFF battery setting)

Illuminance: Illuminance: 1683 lux @ 5 m (OFF battery setting)

Lumens: Lumens: 2220 lm (5-hour battery setting)

Illuminance: Illuminance: 1602 lux @ 5 m (5-hour battery setting)

Lumens: Lumens: 1376 lm (8-hour battery setting)

Illuminance: Illuminance: 992 lux @ 5 m (8-hour battery setting)

Lumens: Lumens: 855 lm (12-hour battery setting)

Illuminance: Illuminance: 613 lux @ 5 m (12-hour battery setting)

Lumens: Lumens: 538 lm (18-hour battery setting)

Illuminance: Illuminance: 385 lux @ 5 m (18-hour battery setting)

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4000 Hz, 6,000 Hz, 25000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 30 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: No

Construction / Physical

Dimensions - Fixture: 4.9 x 4.9 x 6.9 in (126 x 126 x 176 mm)

Dimensions – 6 pack case: 21.8 x 18.5 x 13.5 in (554 x 470 x 345 mm)

Weights:

Weight (single unit): 7.0 LB (3.2 kg)

Weight (shipping weight): 98.3 lbs (44.6 kg)

Exterior Color: Chrome

Housing Material: Aluminum diecast

Connections

Power Connection: 5.5mm right-angle barrel jack

Cable Length (charger): 8.5 ft (2.6m) (sold separately)

Power Input (charging case): Seetronic TRUE1 IP65

Power Output (charging case): Seetronic TRUE1 IP65

Software Connection: USB-C

Control

Control Protocol: RDM, CRMX, NFC, RF

DMX Channels: 5, 8, or 12

Modes/Personalities: 3 personalities (5Ch, 8Ch, 12Ch)

Wireless WDMX “G” Compatibility: G4S

Wireless Lumen Radio Compatibility: CRMX

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Single Unit:

Power and Current (charging): 43 W, 0.74 A @ 100 V, 60 Hz

Power and Current (charging): 42 W, 0.64 A @ 120 V, 60 Hz

Power and Current (charging): 42 W, 0.52 A @ 208 V, 60 Hz

Power and Current (charging): 42 W, 0.47 A @ 230 V, 50 Hz

Power and Current (charging): 42 W, 0.47 A @ 240 V, 50 Hz

6 Pack Case:

Power Linking: 3 units @ 120 V; 4 units @ 208 V; 5 units @ 230 V

Power and Current: 239 W, 3.94 A @ 100 V

Power and Current: 238 W, 3.44 A @ 120 V

Power and Current: 235 W, 2.48 A @ 208 V

Power and Current: 235 W, 2.32 A @ 230 V

Power and Current: 235 W, 2.27 A @ 240 V

Battery

Battery type: Lithium Ion

Rechargeable: Yes

Battery Charge Time: 1.6 hours

Battery Life: 3hr, 5hr, 8hr, 12hr

Battery Power: 25.9 V, 4.4 Ah

Certifications / Qualifications

Certifications: CE, FCC, UKCA

IP Rating: IP65, temporary outdoor/ wet use (fixture)

IP Rating: IP20 (case)

Temperatures:

Temperature (startup): -4 °F to 113 °F (-20 °C to 45 °C)

Temperature (operating): -22 °F to 113 °F (-30 °C to 45 °C)

Optional Accessories

Clamps

WELL FIT X - 15° Filter Pack

WELL FIT X - 60° x 10° Filter Pack

WELL FIT X - Single Charger

WELL FIT X - Black Fixture Cover

W-DMX Micro T-1 TRX G6

What's Included

(6) WELL FIT X

(1) 6 slot charging case

(1) basic RF controller

(1) True 1 power cable

(1) QRG