

Intimidator Beam 360X

Lighting Xcellence is at hand! Unlock it with Intimidator Beam 360X a dynamic, 110-watt compact moving head designed for a variety of mobile events. Robust wireless control options are possible without DMX thanks to the built-in RF receiver that makes Intimidator Beam 360X compatible with the RFC or RFC-XL optional remotes that include options for pan, tilt, color wheel, gobo control and more right in the palm of your hand. This powerhouse also is programmed with a new starting position for the moving head, improving on the whip-around rotation some programming previously initiated, making your programming look smoother and more professional. An impressive 16-facet prism splits the beam and intensifies the excitement and you can project crisp gobos from nearly any distance with the motorized focus. Unlock your X with Intimidator Beam 360X.

HIGHLIGHTS

- Compact moving head designed for mobile events
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Motorized frost filter converts the beam to a wash
- Impressive 16-facet prism splits the beam and intensifies the excitement
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections save setup time
- Fits best in the Intimidator Road Case



SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 14 + white, split colors, continuous scroll at variable speeds
- Gobos : 17 + open (all metal) continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 110 W, (3.9A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 2°
- Illuminance :
(2 m) : 533,551 lux
(5 m) : 85,368 lux
- Lumens : 2,770
- Power Linking : 9 units @ 120 V; 15 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
180 W, 1.5 A @ 120 V, 60 Hz
190 W, 0.1 A @ 230 V, 50 Hz
- Weight : 25 lb (11.4 kg)
- Size : 12.7 x 8.7 x 16.9 in (322 x 220 x 429 mm)
- Approvals : CE, UKCA, RoHS, MET
- Prism : 16-facet round, bi-directional at variable speeds
- Color Temperature : 7500 K
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Intimidator Beam 360X
- Power cord
- PowerCON to bare end (EU only)
- Hanging bracket
- Quick Reference Guide