

Intimidator Free Spot 60 ILS

HIGHLIGHTS

- 100% TRUE wireless, battery-operated moving head spot with built-in D-FI transceiver
- Adjustable run times ensure the fixture will last the length of the event
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- ILS compatibility for use in the ILS ecosystem
- Project crisp gobos from nearly any distance with the motorized focus
- New home position allows for smoother programming
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Fits Best in the CHS-50 Carry Bag



SPECIFICATIONS

- DMX Channels : 8, 10, or 14
- DMX Connectors : 3-pin XLR
- Max Unobstructed Distance : 600 ft (183 m)
- Pan and Tilt : 540°/240°
- Pan and Tilt Ranges : 180°, 360°, 540° pan/90°, 180°, 240° tilt
- Colors : 8 + open, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 metal + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 70 W, (3.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 23 Hz
- Recharge Time : 6.75 hours
- Operating Frequency : 2.412 to 2.484 GHz
- Illuminance :
 - 16,932 lux @ 2 m
 - 9,424 lux @ 2 m
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 110 W, 0.9 A @ 120 V, 60 Hz
 - 107 W, 0.5 A @ 230 V, 50 Hz
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Weight : 22 lb (9.9 kg)
- Size : 9.7 x 10.2 x 11.1 in (246 x 258 x 283 mm)
- Approvals : CE, UKCA , RoHS , FCC
- Prism : 3-facet round static
- Zoom Range (manual) : 13° to 19 °
- Run Time (adjustable) : 4, 6, or 8 hrs
- Recharge Time : 6.75 hours
- Color Temperature : 15,000 K
- Bracket Mounting Hole : M12
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Intimidator Free Spot 60 ILS
- Power cord
- Omega bracket
- Quick Reference Guide