

Intimidator Hybrid 251SR

Enjoy a moving head that can meet all your needs with a true all-in-one light fixture. Intimidator Hybrid 251SR seamlessly morphs from spot to beam to wash. It has 12 + open and split colors with continuous scroll at variable speeds. Harness all the power that moving heads have to offer with Intimidator Hybrid 251SR.

HIGHLIGHTS

- True hybrid moving head fitted with an intense 251 W discharge light engine
- All-in-one light fixture morphs from SPOT to BEAM to WASH effortlessly
- Dual, overlapping prisms with independent control multiply the beam dynamics
- Dual gobo wheels allow for gobo morphing and amazing mid-air projections
- Motorized zoom works in beam, spot and wash modes for ultimate light control
- Unique ¼-turn hanging bracket allows for single or dual clamp mounting options
- Emit crisp projections at almost any distance using the motorized focus
- Glass optics ensure crisp beams and gobos at all times
- Full-color display with RF compatibility, totem mode and onboard memory for storing a scene
- powerCON®-compatible power input/output connections for power linking



SPECIFICATIONS

- DMX Channels : 13 or 19
- DMX Connectors : 3- and 5-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 180°, 360°, 540° pan/90°, 180°, 270° tilt.
- Colors : 12 + open, split colors, continuous scroll at variable speeds
- Gobos : (1) : 9 + open, rotating, indexing, interchangeable, slot-n-lock, continuous scroll at variable speeds
(2) : 17 + open, continuous scroll at variable speeds
- Light Source : Osram SIRIUS HRI® 251W discharge lamp (3,000 hrs)
- Strobe Rate : 0 to 20 Hz
- Power Linking : 3 units @ 120 V; 5 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Gobo Size : 13.7 mm outside, 10 mm image, 0.8 mm max thickness
- Weight : 35.6 lb (16.1 kg)
- Size : 12.6 x 8.6 x 21.6 in (322 x 220 x 549 mm)
- Approvals : CE, MET, ROHS
- Prism (1) : 5-facet round, bidirectional rotation at variable speeds
- Prism (2) : 6-facet linear, bidirectional rotation at variable speeds
- Zoom Angle (beam) : 1° to 3°
- Zoom Angle (spot) : 12° to 23°
- Zoom Angle (wash) : 7° to 19°
- Illuminance (1° beam) : 500,411 lux @ 5 m
- Illuminance (12° spot) : 376,927 lux @ 5 m
- Illuminance (7° wash) : 8,038 lux @ 5 m
- Power and Current : 358 W, 3.6 A @ 120 V, 60 Hz
- Power and Current : 344 W, 2.3 A @ 230 V, 50 Hz
- Optional Controllers : RFC-XL

WHAT'S INCLUDED

- Intimidator Hybrid 251SR
- Power cord
- PowerCON to bare end (EU only)
- Hanging bracket
- Quick Reference Guide