

Intimidator Spot 260X

Unlock Xcellence! Xtreme brightness! Xhilarating colors! Xact control! Intimidator Spot 260X is a 75-watt compact moving head packed with features for easy and powerful lighting design. This innovative mover comes equipped with an updated CTO color wheel and a new moving head home position allows smoother programming and eliminates the starting whip-around action that can be triggered by some programming looks. Convenient control options are also on board with a built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes that provide an array of control options in the palm of your hand. You can also set, save, and recall one scene manually from the full color LCD display. Project crisp gobos from nearly any distance with the motorized focus and tackle short or long throw applications with the manual zoom. The 3-facet prism splits the beam and covers a larger area and beams always remain on the dance floor using the built-in, innovative Totem mode. White housing not available in European Markets.



HIGHLIGHTS

- Compact moving head designed for mobile events
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- ¼-turn hanging bracket allows for quick removal when needed
- Project crisp gobos from nearly any distance with the motorized focus
- Manual zoom for short or long throw applications
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode
- powerCON®-compatible power input/output connections saves setup time
- Fits best in the CHS-2XX VIP Gear Bag
- Available in black or white to fit different applications
- White housing not available in European Markets.

SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/234°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/234°, 180°, 90° tilt
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable
- Light Source : 1 LED (cool white) 75 W, (3.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20Hz
- Power Linking : 7 units @ 120 V; 11 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 124 W, 1.8 A @ 120 V, 60 Hz
 - 128 W, 1 A @ 230 V, 50 Hz
- Weight : 12.2 lb (5.6 kg)
- Size : 9.1 x 6.4 x 13.8 in (232 x 163 x 351 mm)
- Approvals : CE, UKCA, RoHS
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Prism : 3-facet round, static
- Zoom angle (manual) : 12° to 17°
- Illuminance (12°) : 17,458 lux @ 2 m
- Illuminance (17°) : 12,848 lux @ 2 m
- Color Temperature (CTO) : 5,900 K
- Bracket Mounting Hole : 13 mm
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Fixture
- Power cord
- Hanging bracket
- Quick Reference Guide