

Intimidator Spot 360X IP

Bring the power of Intimidator outdoors with Intimidator Spot 360X IP, an outdoor-rated moving head designed for situations where mother nature has different plans for your events. Intimidator Spot 360X IP has a built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes. The water resistant power input/output connections save setup time. A new home position prevents whip around movement when programs are triggered and dual rotating prisms split the beam for great effects and cover a larger area. The power of Intimidator Spot 360X IP is multiplied with motorized focus that lets you project crisp gobos from nearly any distance and beams always remain on the dance floor using the built-in, innovative Totem mode. You can even set, save, and recall 1 scene manually, directly from the full-color LCD display.

HIGHLIGHTS

- Outdoor-rated moving head designed for situations where mother nature gets in the way
- Water resistant power input/output connections save setup time
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Durable magnesium housing is lightweight, strong and corrosion resistant
- Dual rotating prisms split the beam for great effects and cover a larger area
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Fits best in the Intimidator Road Case



SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 100 W, (4.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 15°
- Lumens : 4268
- IP Rating : IP65
- Power Linking : 5 units @ 120 V; 9 units @ 230 V
- Power and Current :
 - 190 W, 2.4 A @ 120 V, 60 Hz
 - 185 W, 1.4 A @ 230 V, 50 Hz
- Weight : 23 lb (10.4 kg)
- Size : 11.8 x 8.5 x 15.9 in (299 x 217 x 406 mm)
- Approvals : CE, MET, UKCA, ROHS
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Prism : 5-facet linear, bi-directional at variable speeds
- Prism : 3-facet round, bi-directional at variable speeds
- Illuminance (2m) : 23,978 lux
- Illuminance (5m) : 3,836 lux
- Color Temperature : 15,000 K
- Startup Temperature : -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature : -22 °F to 113 °F (-30 °C to 45 °C)
- Cable Length : 5 ft (1.5 m)
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Bracket Mounting Hole : 13 mm
- Optional Controllers : RFC, RFC-XL
- Max. Output Current : 12 A (5 units @ 120 V) (9 units @ 230 V)

WHAT'S INCLUDED

- Fixture
- Power cord

- PowerCON to bare end (EU only)
- Hanging bracket
- Quick Reference Guide