

Intimidator Spot 375ZX

Bright and bold! Be your best with X! Intimidator Spot 375ZX is a feature-packed compact moving head designed for large events. 200 watts of lighting power are just the start of the robust and convenient options on board. Along with a color wheel updated with CTO technology, Intimidator Spot 375Z X has a built-in RF receiver for wireless control allows use of the RFC or RFC-XL optional remotes putting unprecedented moving head control options in the palm of your hand without having to aim the remotes at the unit. And Intimidator Spot 375Z X is not only energized, it's motorized! Motorized zoom is on board and is perfect for short or long throw applications and project crisp gobos from nearly any distance with the motorized focus too! A brand new home position allows for smoother programming, eliminating the need for full head rotation to start lighting looks. Dual rotating prisms split the beam for great effects and cover a larger area. Set, save, and recall 1 scene manually, directly from the full color LCD display.



HIGHLIGHTS

- Compact moving head designed for large events
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Dual rotating prisms split the beam for great effects and cover a larger area
- Motorized zoom for short or long throw applications
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections saves setup time
- Fits best in the Intimidator Road Case

SPECIFICATIONS

- DMX Channels : 9 or 15
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 7 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 200 W, (16 A), 50,000 hours life expectancy.
- Strobe Rate : 0 to 20 Hz
- Lumens : 7,161
- Power Linking : 4 units @ 120 V; 8 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 354 W, 3.1 A @ 120 V, 60 Hz
 - 337 W, 1.6 A @ 230 V, 50 Hz
- Weight : 27.2 lb (12.4 kg)
- Size : 12.7 x 8.7 x 18.3 in (322 x 220 x 466 mm)
- Approvals : CE, UKCA, RoHS, MET
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Prism : 5-facet linear, bi-directional at variable speeds
- Prism : 6-facet round, bi-directional at variable speeds
- Zoom Angle (motorized) : 10° to 23°
- Illuminance (10°) : 36,801 lux @ 2 m
- Illuminance (23°) : 21,115 lux @ 2 m
- Color Temperature (CTO) : 5,700 K
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Fixture
- Power cord
- PowerCON to bare end (EU only)
- Hanging bracket
- Quick Reference Guide