

Intimidator Spot 475ZX

This punchy 250W LED powerhouse comes packed with features that make it ideal for installations and precise stage performances. Motorized zoom and focus ensure the looks you create with its dual gobo wheels and dual rotating prisms are always crisp and provide the coverage you need for both short and long throws. With both 3- and 5-pin DMX connectors, Intimidator Spot 475ZX is an easy, powerful addition to any rig.

HIGHLIGHTS

- Compact moving head designed for large events
- Onboard USB-C port allows for quick software updates
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Dual rotating prisms split the beam for great effects and cover a larger area
- Motorized zoom for short or long throw applications
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections saves setup time



SPECIFICATIONS

- DMX Channels : 10 or 16
- DMX Connectors : 3- & 5-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 7 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 250 W, (10 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Lumens : 10,710
- Power Linking : 3 units @ 120 V; 7 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 378 W, 3.4 A @ 120 V, 60 Hz
 - 372 W, 1.9 A @ 230 V, 50 Hz
- Weight : 36.2 lb (16.5 kg)
- Size : 14.3 x 10 x 21 in (363 x 250 x 531 mm)
- Approvals : CE, UKCA, RoHS, MET
- Gobos : 8 + open, indexing, continuous scroll at variable speeds
- Gobo Size : 25.7 mm outside, 21 mm image, 1.3 mm max thickness
- Prism : 5-facet linear, bi-directional at variable speeds
- Prism : 6-facet round, bi-directional at variable speeds
- Zoom Angle (motorized) : 13° to 28°
- Illuminance (13°) : 90,979 lux @ 2 m
- Illuminance (28°) : 24,565 lux @ 2 m
- Illuminance (13°) : 14,557 lux @ 5 m
- Illuminance (28°) : 3,930 lux @ 5 m
- Color Temperature (CTO) : 5,700 K
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Fixture
- Power cord
- PowerCON to bare end (EU only)
- Hanging bracket
- Quick Reference Guide