

SUB2201 SUBWOOFER

Features

The SUB2201 subwoofer is designed to reproduce a smooth and punchy bass on a small footprint. The 6th order bandpass cabinet produces a dry yet deep bass using only a single 10-inch, long-stroke woofer.

This subwoofer is the ideal partner for Biamp Desono speakers in an active setup, with crossover frequencies up to 150 Hz. The black version is equipped with a 35 mm metal adapter on top, allowing stands for placing top cabinets. In order to get the most satisfying sound, it is essential that you read this manual carefully prior to connecting the subwoofer to your system.



Safety Instructions

- Keep this manual for future reference.
- Clean only with dry cloth.
- Do not operate near heaters or place it on other apparatus which produce a lot of heat.
- Take care for the speaker leads. Never use damaged leads and install them in such a way that no one can walk on it.
- Only use accessories specified by the manufacturer.
- Make sure the mounting surface can easily support the speaker's weight.
- Use only industry-accepted rigging tools and methods.
- Choose the right speaker for the right job.
- Use sufficient loudspeakers and avoid death spots.
- Do not connect main power to the subwoofer.
- This apparatus should only be serviced by qualified personnel. If not, the warranty might be void.
- Removal of the grill causes risk to loudspeaker damage.
- Use cables of the right gauge, especially for long runs.
- Use cables with clear colour codes and maintain polarity throughout the whole system.
- Switch amplifiers on with the volumes turned completely down to avoid loud clicks and clacks.
- Avoid loud feedback for this is a main speaker killer.

SUB2201 - SUBWOOFER

UNPACKING

This speaker has been carefully packed at the factory. Open the carton box and remove the speaker from the packing. Do not use sharp objects to open the box. Place the speaker on a flat and stable surface. When the product shows signs of damage caused by transportation, contact your dealer immediately. Damage due to transport and rough handling is not covered by the manufacturer's warranty.

INSTALLATION

It is generally believed that low frequencies are nondirectional and therefore, placement of a subwoofer within the listening room is not critical, however: placing your subwoofer near one or more boundaries, increases the SPL by 3 dB for each boundary (for low frequencies). When using multiple subwoofers, try to place the speakers side by side, this results in 'acoustic' coupling, further increasing the reproduced SPL and punch. Remember: more bass means more speakers.

Placement close to a room corner, will increase the amount of bass output, while placing the subwoofer along the middle of a wall, or out in the middle of a room will decrease the amount of bass output. Experiment with a number of different placement options to find the one that best suits your particular room and musical taste.

Other locations will provide varying degrees of low bass impact and blending with your front speakers. We recommend listening to your system, with the subwoofer in different room positions, to obtain a location with an optimum response.

If you hear too little bass, try moving the subwoofer(s) further towards the room corner or try reversing the polarity of the satellites (phase reverse).

CONNECTION

The subwoofer has no built in crossover or amplifier or protection system. We strongly recommend to use the subwoofer in an active configuration only. Both speakon™ as well as standard speaker wire connectors are provided.

We recommend the use of high quality speaker cable : 2.5 mm² for distances up to 15 meters. For longer distances, use 4 mm² or more.

Note: Music colours our lives but too much sound might damage yours and other's hearing permanently. Being exposed to loud sound levels over a long time can cause severe hearing loss. Don't forget to consult the local law directions regarding producing sound in public places. In some countries ear protection is obliged when the continuous sound level over 8 hours time is 80dB (A).

