

SlimPAR H6 ILS

HIGHLIGHTS

- Low-profile LED PAR with 6-in-1 LED technology (RGBAW+UV)
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave or DMX control (**D-Fi™ USB sold separately**)
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with 6-in-1 LED technology
- Point-and-shoot operation of static colors and automated programs with the optional IRC-6 remote
- Save time running cables and extension cords by power linking multiple units
- Multiple control options include DMX, Master/Slave and Sound-Active modes
- Create customized colors using the built-in LED display
- Achieve smooth LED fading with built-in dimming curves
- Flicker-free operation suitable for on-camera use
- Easily transports in the optional CHS-SP4 VIP Gear Bag
- Sleek and lightweight to easily fit inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 6, 8 or 12
- DMX Connectors : 3-pin XLR
- Light Source : 6 LEDs (hex-color RGBAW+UV) 8 W (1.1A), 50,000 hours life expectancy
- Strobe Rate : 0 to 30 Hz
- Beam Angle : 25°
- Field Angle : 43°
- Illuminance : 1,891 lux @ 2 m
- Power Linking : 14 units @ 120 V; 24 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 41 W, 0.6 A @ 120 V, 60 Hz
 - 41 W, 0.3 A @ 230 V, 50 Hz
- Weight : 2.6 lbs (1.2 kg)
- Size : 7.5 x 3.3 x 8.8 in (192 x 84 x 225 mm)
- Approvals : CE, UKCA, RoHS
- Optional Controllers : IRC6, D-Fi USB
- Bracket Mounting Hole : 13 mm

WHAT'S INCLUDED

- SlimPAR H6 ILS
- Power cord
- Quick Reference Guide