

GigBAR Bridge Beam ILS

It's all happening with GigBAR Bridge Beam ILS, the 3-in-1 pre-mounted lighting rig. Dual moving heads send punchy narrow beams across the dance floor, RGBAW+UV wash lights fill the room with every color from white to blacklight, and dynamic LED rings add dazzling eye candy to your setup. GigBAR Bridge Beam ILS is always ready when you are in its grab-and-go carry bag. Trigger built-in shows with the included RF remote, instantly create coordinated light shows with ILS, and enjoy wireless ILS or DMX control with built-in D-Fi. Captivate the party your way with GigBAR Bridge Beam ILS.

HIGHLIGHTS

- 3-in-1 lighting system that includes moving heads, RGBW rings and washes pre-mounted on a single bar
- Quickly and securely connect multiple fixtures with the built-in locking system
- Built-in DFI transceiver communicates DMX or ILS signals wirelessly
- ILS compatibility for use in the ILS ecosystem
- Safely mounts onto truss or mobile tripods using the removable bracket
- Easy navigation and access all functions directly from the full-color LCD display
- Totem Mode keeps the moving heads focused on the dance floor
- Save time running cables and extension cords by power linking multiple units
- Use the included RF remote to trigger the built-in shows without needing line of sight



SPECIFICATIONS

- DMX Channels : 3, 24 or 60
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 180° 360° 540° Pan / 90° 180° 270° tilt
- Strobe Rate : 0 to 20 Hz
- Operating Frequency : 2.4 GHz
- Power Linking : 9 units @120 V; 18 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 147 W, 1.2 A 120 V, 60 Hz
 - 144 W, 0.6 A 230 V, 50 Hz
- Weight : 16.4 lbs (7.5 kg)
- Size : 25 x 2.6 x 11.4 in (635 x 65 x 290 mm)
- Approvals : CE, RoHS, FCC
- Illuminance (moving head) : 24,670 @ 2 m (per head)
- Illuminance (wash) : 525 Lux @ 2 m (per section)
- Light Source (moving heads) : 2 LEDs (RGBW) 80 W total (2.8 A), 50,000 hours life expectancy
- Light Source (wash) : 4 LEDs (RGBAW+UV) 40 W total (2.6 A), 50,000 hours life expectancy
- Light Source (LED ring) : 48 LEDs (RGBW) 10 W total 50,000 hours life expectancy
- Beam Angle (moving head) : 5°
- Beam Angle (wash) : 20°
- Field Angle (wash) : 37°
- Max Unobstructed Distance (D-Fi) : 600 ft (183 m)
- Fits Tripod Sizes : 1.5 in (37.4 mm)
- Optional Controllers : RF, Footswitch, ILS Command

WHAT'S INCLUDED

- Gigbar Bridge Beam ILS
- Power cable
- PowerCON to bare end (EU only)
- Carrying case
- 2 Hanging brackets
- RF Remote
- Quick Reference Guide