

ILS Command

Light up the night without setting up all day with ILS – which makes creating coordinated light shows across different fixture types easy as 1, 2, 3. No DMX required. Now the ILS universe is at your command with ILS Command, a powerful controller capable of programming any ILS-enabled product. This hardware controller has a built-in D-Fi transmitter that wirelessly controls an unlimited number of ILS-enabled fixtures. Enjoy unlimited creativity as you customize, save and recall presets even in dark environments where backlit silicon buttons provide a tactile response and bright visibility. Your lighting creations are always safe because you can back up, restore and update the controller's software using the built-in USB port and ensure unauthorized access is blocked by enabling the onboard lockout. An innovative follow spot mode highlights grand entrances without interrupting the rest of the show and a built-in audio connector allows for better accuracy when triggering lights to the beat. Manually override the show on the fly using the 9 quick color access buttons



included carry case.

HIGHLIGHTS

- Powerful ILS controller capable of programming any ILS-enabled product
- Built-in D-Fi transmitter controls an unlimited number of ILS-enabled fixtures
- Customize, save and recall presets without using DMX
- Backlit silicon buttons provide a tactile response in dark environments
- Innovative follow spot mode highlights grand entrances without interrupting the rest of the show
- Backup, restore and update the controller's software using the built-in USB port
- Ensure unauthorized access is blocked by enabling the onboard lockout
- Built-in audio connector allows for better accuracy when triggering lights to the beat
- Manually override the show on the fly using the 9 quick color access buttons
- Safely transport the controller with the included carry case

SPECIFICATIONS

- Max Unobstructed Distance : 600 ft (183 m)
- Operating Frequency : 2.412 to 2.484 GHz
- Weight : 3.6 lb (1.6 kg)
- Size : 12.3 x 9.9 x 0.7 in (313 x 252 x 19 mm)
- Approvals : CE, UKCA, RoHS, FCC
- ILS Connectors : 3-pin XLR
- Programmable Presets : 6
- Cable Length : 20 in (508 mm)
- Input Voltage (USB-C) : 5V, 1A

WHAT'S INCLUDED

- ILS Command
- External power supply
- USB-C cable
- Carry bag
- Quick Reference Guide