


Shocker Panel FX IP

Shocker Panel FX IP instantly shifts between strobe, wash, and blinder looks as easily as it moves between indoor and outdoor events. 8 sections of bright RGB color + an intense 8-section cool white LED strip add up to endless eye candy effects from one compact IP66-rated powerhouse. Setups are fast and secure with a digital touch display for choosing dazzling built-in effect macros and setting password access, all with the press of a button. Wherever they take this rugged unit, event managers and entertainers will wow party-goers with Shocker Panel FX IP's high output and fast transitions.

HIGHLIGHTS

- Outdoor-rated versatile blinder, wash and strobe light, with compelling eye candy effects
- Neutrik TRUE1 power input/output connections save setup time while maintaining water resistance
- 16 controllable sections (8 RGB + 8 white) provide creative programming flexibility
- Robust IP-rated housing repels the elements in outdoor situations
- Password-protected and touch-sensitive digital display
- Trigger eye-catching, built-in macros via the display or DMX
- Integrated GORE valve allows the fixture to breathe and prevents internal humidity build-up
- Easily transported in the optional CHS-25 VIP gear bag



SPECIFICATIONS

- DMX Channels : 8, 18, 34 or 47
- DMX Connectors : 5-pin XLR
- Light Source :
 - 480 LEDs (tri-color) 2W, (1A), 50,000 hours life expectancy
 - 32 LEDs (cool white) 1.8 W (0.5 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 119°
- Field Angle : 158°
- Illuminance : 1,131 lux @ 2 m
- Lumens : 13,626
- IP Rating : IP66
- Power Linking : 6 units @ 120 V; 11 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 238 W, 2 A @ 120 V, 60 Hz
 - 231 W, 1 A @ 230 V, 50 Hz
- Weight : 10.4 lbs (4.7 kg)
- Size : 12.9 x 5.1 x 6.8 in (330 x 130 x 173 mm)
- Approvals : CE, ROHS, MET
- Startup Temperature : -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature : -22 °F to 113 °F (-30 °C to 45 °C)
- Cable Length : 5 ft (1.5 m)
- Max Output Current : 12 A (6 units @ 120 V) (11 units @ 230 V)

WHAT'S INCLUDED

- Shocker Panel FX IP
- Power cable
- PowerCON to bare end (EU only)
- Quick Reference Guide