

Vesuvio 4 IP

This IP53-rated vertical fogger creates powerful, illuminated atmospheric bursts with dual-zone RGBA LEDs, delivering a CO₂-style effect without needing compressed gas tanks.

It delivers extreme vertical or horizontal throw for the largest outdoor festivals, touring stages, and indoor environments that demand high-impact, tour-grade atmospheric effects.



- Advanced Vertical Fogger – Creates powerful vertical fog bursts, delivering a CO₂-style effect without the need for gas or tanks.
- Outdoor-Ready Design – Rated for temporary outdoor use, providing reliable operation in wet or damp environments.
- High-Performance Output – Engineered for extreme throw distances of up to 50 ft (15 m), ensuring maximum visual impact.
- Dual-Zone RGBA Illumination – Independently controlled LED zones enable creative color effects and dynamic visuals.
- Rugged Flight Case Included – Ships in a durable touring case for easy transport and protection during rental or live event use.
- Flexible Control Options – Operate via onboard full-color display, wireless RF handheld remote, or DMX integration.
- Integrated Drainage System – Simplifies post-use maintenance with quick water evacuation and easy cleanup.
- USB-C Port – Allows convenient software and firmware uploads for future updates.
- QDF (Quick Dissipating Fluid) Required – Ensures optimal performance and clean atmospheric effects.

SPECIFICATIONS

Optical *

Light Source: 37 LEDs (RGBA)

** These specifications are still being finalized. Speak to a salesperson for more information.*

Dynamic Effects

- Dimmer:** Electronic
- Shutter/Strobe:** Electronic
- Low Fluid Shutdown:** No
- Standalone Color Mixing:** No
- Built-in Automated Programs:** Yes/No

Construction / Physical

- Dimensions:** 20.79 x 13.82 x 17.32 in (528 x 351 x 440 mm)
- Weight:** 72.2 lb (32.75 kg)
- Exterior Color:** Black
- Housing Material:** Aluminum alloy, stainless steel
- Tank Capacity:** 1.4 gal (5.3 l)
- Fluid Consumption:** 22 ml/min
- IP Rating:** IP53
- Heat-up Time:** 13 min
- Maximum Runtime:** 45-second bursts

Connections

- Power Input:** Seetronic Powerkon IP65
- Data Connectors:** 5-pin IP65 XLR
- Cable Length (power):** 5 ft (1.5 m)
- Firmware upgrades:** USB type-C

Control

- Control Protocol:** [DMX, RDM, RF Remote]
- DMX Channels:** 14
- Modes/Personalities:** 1 personalities (14)
- On-Board Control:** Yes
- Included Remote:** yes

Electrical

- Input Voltage:** 208 VAC, 60 Hz
- Power and Current:** 2167 W, 10.43 A @ 208 V, 60 Hz
- Breaker Size:** 16 A, 250 V

Required Accessories

Compatible Mounting Options: [140DX OMEGA BRACKET, M12 BOLT]
Quick Dissipating Fluid (QDF)

Optional Accessories

- CTC-50G
- CTC-50HCN
- RIGLINK POWERKON CABLES
- RIGLINK DMX CABLES

What's Included

- Vesuvio 4 IP
- Seetronic Powerkon Cable
- 2x Omega Brackets
- Controllers: RF Remote