

NC10FXX-14-B

Easy to assemble 8 + 2 pole female XLR connector, black metal housing, secure locking and proven Neutrik chuck type strain relief

Features & Benefits

- Suitable for data offering CAT 5e performance and power up to 16 A and 50 V - exceeds PoE+ capabilities
- Superior ruggedness compared to RJ45 type connectors
- All metal housing offers best overall RF protection and electromagnetic shielding

Technical Information

Product	
Title	NC10FXX-14-B
Connection Type	XLR
Gender	female

All rights reserved / 13.11.2026

NEUTRIK

Electrical	
Contact resistance	≤ 3 mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 10 GΩ (initial); 0.1 (after damp heat test)
Number of electronical contacts	8 + 2
Rated current per contact	16 A (power pins), 3 A (data pins)
Cable shield - shell connection:	N/A
Transmission performance	CAT 5e

Mechanical	
Cable O.D.	8.0 - 10.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	2.5 mm² / AWG 14 (power pins), 1 mm² / AWG 18 (data pins)

All rights reserved / 13.11.2026

NEUTRIK

Material	
Bushing	PA / PU
Contact plating	0.2 µm Au hard alloy over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	PA66
Locking element	Zinc diecast (ZnAl4Cu1)
Locking element plating	Nickel
Shell	Zinc diecast (ZnAl4Cu1)
Shell coating	Black KTL
Strain relief	POM

Environmental	
Flammability	UL 94 V-0
Protection class	IP 40
Solderability	Complies with IEC 60068-2-20
Temperature range	-30 °C to +80 °C
Manufacturing Standard	IEC 61076-2-103

All rights reserved / 13.11.2026